

Bio Tubes

Oil Separator Bioremediation

A new approach to reducing oil discharges in industrial separators.

Place 3 Bio Tubes in a separator to digest up to 6Kg of oil per week for 6-8 months!

The solution to meet both UK consents and European oily water discharge limits.

KEY PROPERTIES

Each Bio Tube contains a blend of oil digesting bacteria and will digest 2 Kg of oil per week per Bio Tube.

Bio Tubes float on the surface absorbing and digesting oil, reducing discharges, BOD and COD (Biological and Chemical Oxygen demands).

- Biological
- Separator Friendly
- Oil Digesting

APPROVALS

- Patent Protected Product
- Petrol Station Approved

TECHNICAL DATA

Appearance	Green Tube packed with oil absorbant & bacteria
Bacteria Type	Euro Type 1
Bacteria Count	4 x 10 ⁹ cfu/g (Cultures Only)

APPLICATION

- Use 3 Bio Tubes per 7000 litre of separator volume. Replace every 6-8 months.
- For use in Forecourt and Industrial Separators, bunds and oily run offs (See approvals).

PACKAGING

Boxes of 3 or 6 Bio Tubes.

SAFE HANDLING

Store before use in a dry area.



For more information or to arrange a demonstration contact

Rozone Limited Queen Street, Darlaston, Wednesbury, West Midlands WS10 8JB
Tel: (0) 121 526 8181 Fax: (0) 121 526 8182 Email: info@rozone.co.uk Web: www.rozone.co.uk

