

Disperse 1040

Oil Slick Dispersant primarily for marine use on fuel and crude oils

A blended oil slick dispersant approved for marine use.

KEY PROPERTIES

Suitable for use on most oils spills at sea, but particularly optimised for fuel oils.

Contains less than 3% aromatic hydrocarbons.

Requires no special storage or handling precautions.

APPROVALS

- Warren Spring specification LR448 (OP)
- Type 2/3 Oil Slick Dispersant (approved by MAFF and Dept Agriculture and Fisheries for Scotland).

TECHNICAL DATA

S.G.	1.01
VOC	Zero
pH	6.5 – 7.0
Freezing Point	-15°C
Miscible in sea water	

APPLICATION

- Use as supplied. 1 part Disperse 1040 will treat up to 25 parts oil depending upon oil type and prevailing conditions.
- As a Type 2 Dispersant (water soluble concentrate) Disperse 1040 is best used as a 10% solution in water.
- As a Type 3 Dispersant apply direct using spray equipment from aircraft or ships or spray directly onto oil on beaches.
- The Type 3 mode is normally preferred because of the enhanced efficiency when used as a concentrate.

PACKAGING

1000Ltr, 200Ltr.

SAFE HANDLING

Store in original containers and avoid extremes of temperature.



For more information or to arrange a demonstration contact

Rozone Limited Queen Street, Darlaston, Wednesbury, West Midlands WS10 8JB

Tel: (0) 121 526 8181 Fax: (0) 121 526 8182 Email: info@rozone.co.uk Web: www.rozone.co.uk

