

Sobo LF

Tunnel and Spray Wash Cleaning

The move away from using greenhouse gas producing cleaning solvent has started! Sobo LF is solvent free, VOC free and environmentally friendly. Used in high pressure spray tunnels and power wash systems to provide an oil free clean surface.

KEY PROPERTIES

Sobo LF is a rust inhibited quick break aqueous cleaning fluid that is non emulsifiable (quick break), low foaming, inhibited and offering no hazard to painted surfaces, acrylics, non-ferrous metals and soft sealants.

- Quick Break
- Low Foam
- Rust Inhibited

APPROVALS

- Rust Inhibited - AMS 1526B
- Separator Friendly - pr EN 858

TECHNICAL DATA

SG at 20°C	1.03
VOC	Free
pH	7.5 – 8.5
BOD/COD 5 day	72%

APPLICATION

- Suitable for use in spray wash systems such as tunnels, parts washers and steam cleaners.
- Dilute between 2 – 5% depending upon the degree of soiling and the level of corrosion inhibited required.
- Dilutions below 1:1 are not classified as hazardous.

PACKAGING

1000Ltr, 20Ltr, 4x5Ltr and Wipe Format.

SAFE HANDLING

Store in original containers and avoid extremes of temperature.



For more information or to arrange a demonstration contact

Rozone Limited Queen Street, Darlaston, Wednesbury, West Midlands WS10 8JB
Tel: (0) 121 526 8181 Fax: (0) 121 526 8182 Email: info@rozone.co.uk Web: www.rozone.co.uk

